

Round-dowel level indicator



Square-dowel level indicator



Mod.166-ER EN ASME/ANSI Round-dowel level indicator box

Connection: Round-dowel Ø 20 mm.
Box n°: 0 to X
Material: ■ Cast steel. PN-16. PN-40
■ Stainless steel. PN-40

For use in boilers, receivers, cisterns, reservoirs, ...etc., to control the level of liquids, gases and steam.
A multiple-slot polyprismatic viewer allows the level to be optically read, clearly differentiating liquid and gas phases from liquid ones.

Depending on version



Mod.166-EC EN ASME/ANSI Square-dowel level indicator box

Connection: Square-dowel □18 mm.
Box n°: 0 to X
Material: ■ Cast steel. PN-16. PN-40
■ Stainless steel. PN-40
Blowoff valve: Mod. 999 3/8" with simple joint plug

For use in boilers, receivers, cisterns, reservoirs, ...etc., to control the level of liquids, gases and steam.
A multiple-slot polyprismatic viewer allows the level to be optically read, clearly differentiating liquid and gas phases from liquid ones.

Depending on version



Mod.666 EN ASME/ANSI Level gauges

Connection: Flange
DN: 20 and 25
Material: ■ Cast steel. PN-16
■ Cast steel. PN-40
■ Stainless steel. PN-40
Seal: ● Metal
Blowoff valve: Mod. 999 3/8" with simple joint plug

Mod.466 EN ASME/ANSI Level gauges

Connection: Flange
DN: 20 and 25
Material: ■ Cast steel. PN-16
■ Cast steel. PN-40
■ Stainless steel. PN-40
Seal: ● Metal