

Steam traps

Mechanical

Float and thermostatic steam trap





241



243

244

Mod. 241 EN ASME/FNPT

Connection: Female thread GAS
Female thread NPT
R: 1/2" to 1"
Material:  Cast iron. PMS-14 bar
Seal:  Metal

Mod. 243 EN ASME/FNPT ASME/SW

Connection: Female thread GAS
Female thread NPT
Socket welding ends SW
R: 1/2" to 1", 1 1/2" and 2"
Material:  Cast steel. PMS-14 bar
Seal:  Metal

Mod. 244 EN ASME/ANSI

Connection: Flange x Flange
DN: 15 to 25, 40 and 50
Material:  Cast steel. PMS-14 bar
Seal:  Metal

To extract saturated or super-heated medium or low-pressure steam condensates.
Applicable to: steam piping, heat exchangers, plants with automatic temperature control, etc., in the chemical and petrochemical industries, etc.



Depending on version



Inverted bucket steam trap



Mod. 343 EN ASME/FNPT

Connection: Female thread GAS
Female thread NPT
R: 1/2" to 1"
Material:  Cast iron. PN-16
Cierre:  Metal

To extract saturated or super-heated low-pressure steam condensates.

Applicable to: steam piping, heat exchangers, plants with automatic temperature control, etc., in the chemical and petrochemical industries, etc.

Depending on version

