

Safety ASME

Full lift safety valve with spring loading. (AIT)



EP

AP

ES

AS

Mod. 885 CRYOGENIC

Connection: Male thread NPT x Female thread NPT
MNPT1 x FNPT2: 3/8"x1/2" to 1"x1"

Material: ■ Bronze. PMS-522, 14 psi

■ Stainless steel. 300 lbs

Seal: ● PTFE (Teflon)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.

Design in accordance with "ASME code section VIII Div.1".

Materials according ASME code section II and ASTM.
Connections according ASME B1.20.1 standard.

Depending on version



-320,8°F to +392°F



2,90 psi to 522,14 psi



Steam/Gases/Liquids



EP

AP

ES

AS

Mod. 985

Connection: Male thread NPT x
Female thread NPT

MNPT1 x FNPT2: 3/8"x1/2" and 1/2"x1/2"

Material: ■ Stainless steel. 900 lbs

Seal: ○ PTFE (Teflon)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.

Design in accordance with "ASME code section VIII Div.1".

Materials according ASME code section II and ASTM.
Connections according ASME B1.20.1 standard.

Depending on version



-76°F to +392°F



523,58 psi to 2.088,57 psi



Gases