



PED 2014/68/EU CATEGORIZATION

PED 2014/68/UE CATEGORIZACIÓN

PED 2014/68/UE CATÉGORISATION

PED 2014/68/EU KATEGORISIERUNG

STOP VALVE WITH BELLOW SEALS

VÁLVULA DE INTERRUPCIÓN CON FUELLE DE ESTANQUEIDAD

ROBINET A SOUPAPE D'ARRÊT À SOUFFLET

ABSPERRVENTIL MIT FALTENBALGADICHTUNG

248

| MATERIAL | SIZE | PS | FLUID | GROUP | CATEGORY | MODULE |
|---------------------------------|-------|--------|--------------|-------|--------------|--------|
| Nodular casting | DN15 | 16 bar | Gas / Liquid | 1 | Art.4, par.3 | SEP |
| | DN20 | | | | Art.4, par.3 | SEP |
| | DN25 | | | | Art.4, par.3 | SEP |
| | DN32 | | | | I | H |
| | DN40 | | | | I | H |
| | DN50 | | | | I | H |
| | DN65 | | | | II | H |
| | DN80 | | | | II | H |
| | DN100 | | | | II | H |
| | DN125 | | | | II | H |
| | DN150 | | | | II | H |
| | DN200 | | | | II | H |
| Carbon steel Stainless steel | DN15 | 40 bar | Gas / Liquid | 1 | Art.4, par.3 | SEP |
| | DN20 | | | | Art.4, par.3 | SEP |
| | DN25 | | | | Art.4, par.3 | SEP |
| | DN32 | | | | II | H |
| | DN40 | | | | II | H |
| | DN50 | | | | II | H |
| | DN65 | | | | II | H |
| | DN80 | | | | II | H |
| | DN100 | | | | II | H |
| | DN125 | | | | III | H |
| | DN150 | | | | III | H |
| | DN200 | | | | III | H |